

SAFETY DATA SHEET

SECTION 1

MATERIAL IDENTIFICATION

PRODUCT NAME / DESCRIPTION: Industrial Floor Cleaner

DISTRIBUTED / MANUFACTURED BY:

Temco Ind., Inc.
1180 Brookside Ct.
Edmond, OK 73025

Date: 3/10/21
Phone: (800) 245-1869
Emergency Phone: (800) 255-3924

FUNCTION Industrial Cleaner

SECTION 2

HAZARD IDENTIFICATION

CLASSIFICATION:

Acute Toxicity:	Category 3
Skin Corrosion/Irritation:	Category 2
Serious Eye Damage/Eye Irritation:	Category 2
Respiratory Sensitizer:	Category 1
Skin Sensitizer:	Category 1
TOST:Acute	Category 3
Aspiration:	Category 1
Aquatic Toxicity: Acute	Category 2
Aquatic Toxicity: Chronic	Category 2

SIGNAL WORD:

WARNING!

HAZARD STATEMENTS:

- Toxic if swallowed.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- May be fatal if swallowed and enters airways.
- Toxic to aquatic life.
- Toxic to aquatic life with long lasting effects.



PRECAUTIONARY STATEMENTS

Obtain Special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well ventilated area.
Wash all exposed skin thoroughly after handling.
Avoid release to the environment.
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Keep container tightly closed.
Keep only in original container.
Do not get in eyes, on skin, or on clothing.
Do not eat, drink, or smoke when using this product.

TOXICITY:

See Section 11

SECTION 3

HEALTH HAZARDS

CHEMICAL NAME	%W/W	CAS NUMBER
1-Butoxy-2-Propanol	<10	5131-66-8
Isopropanol	<10	67-63-0
Benzenesulfonic acid, C10-16 alkyl derivative	<10	68584-22-5
Potassium Hydroxide (Proprietary Formula)	<5	1310-58-3

SECTION 4

FIRST AID

Potential acute health effects:

Eyes: May cause severe irritation, burns, and/or damage
Skin: May cause severe irritation, burns, and/or damage
Inhalation: Inhalation may cause severe irritation
Ingestion: Ingestion may cause irritation, corrosion/ulceration, nausea, and vomiting.

Medical conditions aggravated by exposure:

None known.

Eye Contact: In case of contact, immediately flush eyes with cool running water. Lift and separate eyelids while flushing with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation occurs. Wash clothing before reuse. Destroy contaminated shoes.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms develop.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Give plenty of water.

SECTION 5**FIRE FIGHTING MEASURES**

Fire Hazard Classification (OSHA/NFPA): 1
Extinguishing Media: As required for fire being fought.
Special Fire Fighting Procedures: Use self-contained breathing apparatus.
Hazardous Combustion Products: None known.

SECTION 6**ACCIDENTAL RELEASE MEASURES**

Personal Precautions, PPE, and Emergency Procedures: Wear protective clothing as described in Section 8 of this safety data sheet.

Containment Procedures: Stop the flow of material, if this is without risk. Wear appropriate protective equipment and clothing during clean-up. Do not allow the spilled product to enter public drainage system or open water courses.

Clean-Up Procedures: Sweep up or gather material and place in appropriate container for disposal. Wash spill area thoroughly. Wear appropriate protective equipment during cleanup. Dispose of collected material according to regulations.

SECTION 7**HANDLING AND STORAGE**

Handling: Avoid contact with eyes, skin, and clothing. Do not take internally. For industrial use only. Wash after handling. Don't breath dust, vapor, or gas. Keep this and all chemicals out of reach of children.

Storage: Keep away from heat, sparks, and open flames. Prevent spills. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Empty product containers may contain product residue, do not reuse.

SECTION 8**PERSONAL PROTECTION / EXPOSURE CONTROLS**

Ventilation System: Always keep exposure below permissible exposure limits. In general dilution ventilation is a satisfactory health hazard control for this substance. However, if conditions of use create discomfort to the worker, a local exhaust system should be considered.

Airborne Exposure Limits: None Established.

Personal Protection: As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1920.132), employers must perform a Hazard Assessment for all workplaces to determine the need for, and selection of, proper protective equipment for each task performed.

Eyes: Wear face shield, safety glasses, or chemical goggles.

Hands & Skin: For prolonged or repeated handling, use impervious gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

Respiratory: If ventilation is not sufficient appropriate NIOSH/MSHA respiratory protection must be provided.

Work Practices: Eye wash fountain and emergency showers are recommended.

SECTION 9

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Liquid
Color:	Clear yellow/green
Odor:	Alcohol-like
Odor Threshold:	NE
pH:	11.67 +/- 0.5
Boiling Point:	NE
Melting Point:	NE
Flash Point:	NE
Evaporation Rate (Butylacetate=1):	NE
Flammability:	Non-Flammable
UEL:	NE
LEL:	NE
Vapor Pressure:	NE
Vapor Density:	NE
Specific Gravity (Water=1):	1.10 +/- 0.05
Solubility Water:	Soluble
Partition Coefficient:	NE
Auto-ignition Temperature:	NE
Decomposition Temperature:	NE
Viscosity (CPS):	NE

SECTION 10

STABILITY AND REACTIVITY

Stability: This product is stable under normal temperatures and pressures.
Incompatibility: Strong Acids
Decomposition Products: Unknown
Conditions to Avoid: Extreme Heat

SECTION 11

TOXICOLOGICAL PROPERTIES

Raw Material	Test	Result	Route	Species
1-Butoxy-2-Propanol (5131-66-8)	LD50	2700 mg/kg	Oral	rats
Isopropanol (67-63-0)	LD50	400 mg/kg	Oral	rats
Benzenesulfonic acid, C10-16 alkyl	LD50	530 mg/kg	Oral	rats
Potassium Hydroxide (1310-58-3)	LD 50	273 mg/kg	Oral	rat

See Section 4 for symptoms.

CARCINOGENICITY

No known carcinogens.

MUTAGENICITY:

No known mutagens.

REPRODUCTIVE TOXINS:

No known reproductive toxins.

SECTION 12

ECOLOGICAL INFORMATION

Raw Material	Test	Result	Time	Species
1-Butoxy-2-Propanol (5131-66-8)	LC50	560 mg/l	96 hrs	Guppy
Isopropanol (67-63-0)	LC50	>5000 mg/L	96 hr	Carassius Auratus
Benzenesulfonic acid, C10-16 alkyl	N/A			
Potassium Hydroxide (1310-58-3)	LC50	80 mg/L	24 hrs	Mosquito Fish

PERSISTENCE & DEGRADABILITY:

NE

BIOACCUMULATION:

NE

MOBILITY:

NE

SECTION 13

DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved

waste disposal facility. Processing, use, or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose container and unused contents in accordance with federal, state, and local requirements.

SECTION 14

TRANSPORT INFORMATION

Not a regulated substance.

SECTION 15

REGULATORY INFORMATION

US FEDERAL REGULATIONS

SARA (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

SARA 302 EXTREMELY HAZARDOUS SUBSTANCES LIST: N/A

SARA 312 HAZARD CATEGORY: N/A

SARA 313 TOXIC CHEMICALS LIST: N/A

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT):

N/A

RCRA (RESOURCE CONSERVATION AND RECOVERY ACT) LISTED HAZARDOUS WASTES:

N/A

CWA (CLEAN WATER ACT) LISTED SUBSTANCES:

N/A

FDA (FOOD AND DRUG ADMINISTRATION):

N/A

TOXIC SUBSTANCES CONTROL ACT (TSCA):

ALL INGREDIENTS ARE LISTED.

NFPA HAZARD INFORMATION SIGN:

[2] HEALTH HAZARD (BLUE DIAMOND)

- 4-DEADLY
- 3-EXTREME DANGER
- 2-HAZARDOUS
- 1-SLIGHTLY HAZARDOUS
- 0-NORMAL MATERIAL

[1] FIRE HAZARD (RED DIAMOND)

- FLASH POINTS:
- 4-BELOW 73 F
 - 3-BELOW 100 F
 - 2-BELOW 200 F
 - 1-ABOVE 200 F
 - 0-WILL NOT BURN

[1] REACTIVITY HAZARD (YELLOW DIAMOND)

- 4-MAY DETONATE
- 3-SHOCK AND HEAT MAY DETONATE
- 2-VIOLENT CHEMICAL CHANGE
- 1-UNSTABLE IF HEATED
- 0-STABLE

[] SPECIFIC HAZARD (WHITE DIAMOND)

- | | |
|------|--------------|
| OX | OXIDIZER |
| ACID | ACID |
| ALK | ALKALI |
| COR | CORROSIVE |
| W | USE NO WATER |

SECTION 16

OTHER INFORMATION

THIS INFORMATION IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.